

Low Voltage Termination Kit

Jointmaster's range of low voltage heat shrink cable terminations covers the full size range of 3 and 4 core, 600 / 1000 volt and 3,3kV cables.

Offering excellent protection against water ingress and environmental damage.

All materials used in the terminations are UV stabilised for long term performance.

These terminations are suitable for both indoor and outdoor applications.

Standard tail length is 400mm. Other tail lengths are available upon request.

Solderless earthing kits are also available to suit these terminations.

TYPE TESTING		
TEST	REQUIREMENT	RESULTS
Initial Insulation Resistance	> 50 M	Complied
Initial Voltage Withstand 4kV 1min	No Breakdown	Complied
Impact Test	No Cracks or damage	Complied
Insulation Resistance After impact test	> 50 M	Complied
Load Cycling Test 100 cycles @ 85°C	No Breakdown	Complied
AC Voltage Withstand 4kV 15 min	No Breakdown	Complied
Insulation Resistance Immersed	> 50 M	Complied

Three Core	
Kit Ref	Cable Size
JHT3/616	6 - 16mm ²
JHT3/1635	16 - 35mm ²
JHT3/50120	50 - 120mm ²
JHT3/150300	150 - 300mm ²

Four Core	
Kit Ref	Cable Size
JHT4/616	6 - 16mm ²
JHT4/1635	16 - 35mm ²
JHT4/50120	50 - 120mm ²
JHT4/150300	150 - 300mm ²

Standard tail lengths available; 300mm, 400mm, 600mm, 800mm, 1000mm and 1200mm.

Setting the Standards in Cable Jointing